

SOFTLIGHT



Advance Lighting



Code:RGB-55

INTRODUCTION

New idea stage lighting Three-basic color softlight
Designed for Small or middle-sized studio, Conference room,
Specially suitable for School Hall, Small studio & News studio,
Exhibitions, Showroom, Church.

SPECIFICATIONS

Economizing electronic energy by more than 75%
*Dimmable Ballast 0-100% frequencies in the Range of 25k-35kHz
The Luminaire has two locking 5-pole XLR connectors for serial data
Transfer,It responds to command signals conforming to the USITT
DMX512 (1990) standard. Body : Aluminium
PLC compact fluorescent lamp temperature color arrival
Reappearing lamp color exponent 90 (Ra)
3000k warm (Halogen), 5400k cool (Day light)
Rated average Life more than 10000 hours
Nearest incandescent equivalent wattage 55w=300w lumens 5000
Optical features: 3000k (Warm 55w x 4) 1.5metre 1000Lx. 1m. 1500Lx.
(Warm 55w x 2) 1.5metre 800Lx. 1m. 1000Lx.
5400k (Day Light 55w x 4) 1.5m. 1100Lx. 1m. 1600Lx.

On Request:4-leaf barndoors, Safety guard, Safety chain, Clamp
12ch. DMX Lighting Control console,

Input Power: 220V. 50Hz.

Light size:

RGB-55w x 4 605 x 365 x 150mm
RGB-55w x 2 605 x 240 x 150mm

Weight:

RGB-55w x 4 8kg.
RGB-55w x 2 6kg.

